



FIRE RATED PRODUCTS

CEASE FIRE SELF CLOSING VENT OVERVIEW



PRECISION EMBER GUARD: The specialized mesh is designed to catch and neutralize wind-driven micro-embers before they can penetrate your structure.

THERMAL ACTIVATION: Equipped with advanced fire-blocking technology, the vent is engineered to self-seal at 390°F (approx. 199°C). * **Oxygen Suppression:** Once triggered, the vent creates a physical seal that chokes off the flow of oxygen, preventing flames from entering the attic or crawlspace.

ARCHITECTURAL INTEGRATION: Designed to disappear into your home’s aesthetic without sacrificing the rigorous safety standards required for **WUI (Wildland-Urban Interface)** compliance.

THE CEASE FIRE ADVANTAGE: While standard vents act as an open door for fire, our vents act as a sentry—closing the gate the moment heat hits the threshold.

NO VISIBLE FASTENERS

Achieve a clean, high-end architectural finish with our proprietary hidden-mount system.

SEAMLESS AESTHETIC: Designed to integrate perfectly into the building’s exterior without the distraction of exposed screws, rivets, or hardware.

FLUSH-MOUNT DESIGN: Provides a smooth, professional appearance that complements high-end stucco, fiber cement, and wood siding applications.

SECURITY: By eliminating visible fasteners, the vents are more resistant to tampering while maintaining a sophisticated, “built-in” look.

Tested & Certified By Cal Fire Cease Fire Cal Fire #8165-2394:0001 Ember ASTM E2886M-20/E2886 Vertical ASTM E2912 Horizontal ASTM E2912-17 Complies with California Title 24 Chapter 7. California’s Building Code (CBC) 1.11.2.4

FINISHES

Standard Finish Clear Anodized Aluminum
Black Anodized, Dark Bronze & Medium
Bronze Available. Powder Coat Colors Offerd

MATERIAL

MATERIAL: Aluminum Alloy 6063 T5 ASTM: B221
THICKNESS: Nominal .050
LENGTH: Standard 10 ft.
FINISH: Standard-Clear anodized
Architectural 200R1 Medium Etch AAM32C10A21



FIRE RATED PRODUCTS

CEASE FIRE SELF CLOSING VENT OVERVIEW



DESCRIPTION

PART ID	REVEAL WIDTH	LENGTH	ROUGH OPENING LENGTH	ROUGH OPENING WIDTH	VENT AREA	% OF VENT AREA
CF75-V-425-17	4-1/2"	17"	17-1/2"	5-1/2"	5 sq. in./ Ln. Ft.	0.143
CF75-V-425-3	4-1/2"	3ft	36-1/2"	5-1/2"	5 sq. in./ Ln. Ft.	0.143
CF75-V-425-4	4-1/2"	4ft	48-7/8"	5-1/2"	5 sq. in./ Ln. Ft.	0.143
CF75-V-425-5	4-1/2"	5ft	59-7/8"	5-1/2"	5 sq. in./ Ln. Ft.	0.143
CF75-V-425-6	4-1/2"	6ft	73-5/8"	5-1/2"	5 sq. in./ Ln. Ft.	0.143
CF75-V-425-7	4-1/2"	7ft	84-5/8"	5-1/2"	5 sq. in./ Ln. Ft.	0.143
CF75-V-425-8	4-1/2"	8ft	97"	5-1/2"	5 sq. in./ Ln. Ft.	0.143
CF75-V-425-10	4-1/2"	10ft	120-1/2"	5-1/2"	3 sq. in./ Ln. Ft.	0.143

Vents are available in factory-standard foot increments only; field modifications are not permitted.